



A-43/2 Nariana Industrial Area
Phase 1, Near PVR Cinema Hall
New Delhi 110028, India
Phone: 011-45612987
Website: www.elan.in

Product Specification Sheet

Pattern: Verve

Date: 06/ 22/ 2011

ENCORE by The Symphony Collection

General Specifications

Weight (linear yard)	16.5 oz
Width	54"
Total Thickness	0.85 mm
Surface Composition	Polyurethane 100%
Substrate Composition	Polyester 100%

General Treatments

Hydrolysis Resistance	5 yrs	ISO 1419:1995 (Jungle Test)
UV Resistance	200 Hours	CFFA-2 / ASTM G26-96 Method C
Hydrolysis	5 years	
Cold Crack	-20 F	CFFA-6 Federal Standard No. 191A-Method 5874
Stain Resistance	Yes	

Physical Strength Properties

Abrasion	500,000+ DR		CFFA-1A/ Method ASTM D 4157-92
Tear Strength	7.9 Warp	9.3 Fill	CFFA-16/ ASTM D751-07a
Breaking Strength	125 Warp	117 Fill	CFFA-17/ ASTM D751-06
Seam Strength Tack Tear	48 Warp	47 Fill	CFFA-14/ Method ASTM D751-06
Blocking Resistance	1 Rating		CFFA-4/ FTMS 191A-TM5872
Crocking	4.5 Dry	4.5 Wet	AATCC-Method 8-2001

Flame Retardancy Standards

California Technical Bulletin 117	Pass	NFPA 260	Pass
UFAC Class I	Pass	IMO A.652(16)8.2	Pass
BIFMA CS-191-53, Section 3	Pass	California 1350	Pass
BIFMA Upholstery, Section 4	Pass		